

Polyetheramine D-2000

Polyetheramine D-2000

| | | |
|--------------|-----------|-----------|
| PRODUCT CODE | CAS NO. | ISSUED |
| RS-D2000 | 9046-10-0 | July 2026 |

§1 PRODUCT DESCRIPTION

A difunctional primary polyetheramine (~2000 MW) used as an epoxy curing agent, flexibilizer and intermediate.

§2 TYPICAL PROPERTIES

| PROPERTY | SPECIFICATION | TYPICAL VALUE |
|---------------------------|---------------|----------------------------|
| Appearance | — | Liquid |
| Color (Hazen) | — | Colorless to slight yellow |
| Boiling point/range (°C) | — | >250 °C |
| Flash point (°C) | — | 185 °C (closed cup) |
| Vapour pressure (20 °C) | — | 0.9 hPa |

PACKAGING

Standard industrial packaging; drum, IBC, or bulk options quoted per order.

DOCUMENTATION

Full SDS available on request. Lot-specific CoA ships with every order.

Values shown are typical of recent production and do not constitute a sales specification; the lot-specific Certificate of Analysis governs for any shipment. Product is supplied for industrial use only.

Typical batch values, provided in good faith. Contact solutions@rawsource.com for batch-specific data.