

# Polydimethylsiloxane Fluid, 350 cSt

Polydimethylsiloxane (silicone fluid), 350. cSt

PRODUCT CODE	CAS NO.	ISSUED
RS-SIL100ST350	63148-62-9	July 2026

## §1 PRODUCT DESCRIPTION

A linear polydimethylsiloxane fluid with a nominal viscosity of 350 cSt at 25 °C.

## §2 TYPICAL ANALYSIS

PROPERTY	SPECIFICATION	TYPICAL RESULT
Acid Value	—	0.050 mg KOH/g
Appearance	—	Clear, colourless liquid
Volatile Content	—	0.84 %
Nominal Viscosity at 25 °C (cps)	—	350
Volatile Loss (1hr at 150 °C) (%)	—	<2
Specific Gravity at 25 °C	—	0.967
Refractive Index at 25 °C	—	1.405
Flash Point Open Cup ( °C)	—	>260

Lot-specific CoA ships with every order.

### PACKAGING

Standard industrial packaging; drum, IBC, or bulk options quoted per order.

### DOCUMENTATION

Full SDS available on request. Lot-specific CoA ships with every order.

Values shown are typical of recent production and do not constitute a sales specification; the lot-specific Certificate of Analysis governs for any shipment. Product is supplied for industrial use only.

Typical batch values, provided in good faith. Contact [solutions@rawsource.com](mailto:solutions@rawsource.com) for batch-specific data.